

## **Anti Graffiti Cold Laminating Film**

## **Product Information**

Construction - PET (Polyester) Usage - PSA Cold Laminating

Film Thickness - 38 microns

Adhesive Thickness - 25 microns Solvent based acrylic (permanent) pressure sensitive adhesive

Total Thickness - 63 microns

Liner Thickness - 100 gsm double sided PE coated paper

PH - Absolute neutral

**UV Coating - YES** 

UV Stability - 1.0 PHR

Shrinkage - NIL

Stick Factor - #10 (Ball)

Outdoor Life - up to 5 years\*

Finish - Gloss

Core - 76mm

**Shelf Life:** 1 year (stored up to 25°C and 50% relative humidity), in original packing of the box.

PLEASE NOTE – All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the "information") shall be used only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchase should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. The seller shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser's reliance on the information.



<sup>\*</sup> Outdoor life will vary depending on position climate and application.