

DOUBLE SIDED MATT SYNTHETIC FILM

210 Micron double sided printable synthetic film with a matt finish. It is ideal for double sided and water proof posters and double sided hanging banners. Suitable for Latex and UV Curable inks.

PRODUCT FEATURES

Blockout layer for double sided printing Indoor / Outdoor advertising Compatable with latex, and UV ink Excellent colour reproduction Fast dying

TECHNICAL DATA


Test Term=	Unit	Test Method	Average
Weight-	g/m²	GB/T4669	190±20
Tensile strength at MD	N/5cm	GB/T1040	200
Tensile strength at CD	N/5cm	GB/T1040	300
Applicable Temperature	`=		-20~+70

o

INSTALLATION

We suggest you allow 24-48 hours for the print to dry prior to lamination. Always clean application free of dust, dirt, debris and other contaminants. We recommend cleaning the installation surface with isopropyl alcohol prior to application.

All information stated within this Product Data Sheet is intended for reference purposes only The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.



Unit 22 / 1029 Manly Rd, Tingalpa QLD 4173 P (07) 3890 5414 F (07) 3890 5701 ABN 49 163 849 232 ACN 163 849 232

creativegraphicsupplies.com.au