

PRODUCT DATA SHEET

CGML360 PREMIUM MESH WITH LINER

CG Mesh is a PVC Banner mesh with removable liner. 360 GSM, 1000 x 1000 denier, 12 x 12 yarn. Its ideal for building and construction wraps, general fence signage and advertising banners in high wind areas. Suitable for Solvent Eco-Solvent, UV and Latex ink technologies.

APPLICATIONS

- Fence Signage
- Banners in High Wind Areas

TECHNICAL DATA

Testing condition: Indoor temperature 23±2°C, Relative humidity 50±5%.

Test Term	Unit	Testing Method	Average
Base Fabric Yarn	Denier	GB/T16604	1000DX1000D
Base Fabric Density	Thread/inch	FZ/T01003	12X12
Finished Fabric Weight	Gram/m ²	GB/T4669	360±20
Tensile Strength at MD	N/5cm	GB/T1040	≥1300
Tensile Strength at CD	N/5cm	GB/T1040	≥1000
Tearing Strength at MD	N/5cm	GB/T16578	≥100
Tearing Strength at CD	N/5cm	GB/T16578	≥80
Temperature Range	°C		-20 ~ +70

All technical data is subject to change without prior notice

We suggest you allow 24-48 hours for the print to dry prior to installation. Always clean application free of dust, dirt, debris and other contaminants. We recommend cleaning the installation surface with isopropyl alcohol prior to application.

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.