

PRODUCT DATA SHEET

3mm Foam PVC With Dual Liners

Bright white 3mm printable foam pvc sheets covered both sides with PE Film for protection. Uv printing compatible

PRINT

- UV Printing
- Screen Printing
- Engraving

FEATURES

- Moisture-proof, mildew-proof, non-corrosion, non-absorbent, and have good shock-proof effect.
- Light weight and convenient for storage, transportation and construction.
- Good plasticity, being an excellent thermoform material.
- Stable color retention.
- Self-extinguish

TECHNICAL DATA

Test Items	units	Average value
Thickness-finished product	mm	1-20
Density	g/m ³	0.35-0.9
Tensile Strength	Mpa	11-20
Elongafion at Break	%	13-20
Impact Strength	kJ/m ²	8-15
Service temperature range		-20~+80

Application requirement:

- Printing
- Temperature of 25 ± 5 ° C, relative humidity of 50% ± 10%
- Clean dust-free environment
- Adjust the printer mode to the best condition before printing

Storage condition:

- Temperature of 10~25° C, relative humidity of 50% ± 10%
- Store in the original packing and with the original protection materials

We suggest you allow 24-48 hours for the print to dry prior to installation. Always clean application free of dust, dirt, debris and other contaminants. We recommend cleaning the installation surface with isopropyl alcohol prior to application.

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.