







DATA SHEET- EDGE-It® TAPE

A PET REINFORCED CARRIER COATED WITH A HIGH PERFORMANCE ADHESIVE TAPE

SUBSTRATE

CHARACTERISTIC	VALUE
COMPOSITION	1000D*1000D 23CMS X 23CMS
WEIGHT	500 GM2 +/- 5%
BREAKING STRENGTH (N/5cm)	1300
TEMPERATURE RESISTANCE	-30°C TO 70°C

ADHESIVE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC
TACK	J.DOW NO. 24
CARRIER	PET
PEEL ADHESION	PSTC-3 1.8KGS/25MM
SHEAR STRENGTH	PSTC-7 OVER 24 HOURS WITH 1KG LOADING
	ON 25MM X 25MM AT 25°C
SERVICE TEMPERATURE	-20°C TO 90°C

PRODUCT FEATURES AND APPLICATIONS

П

HIGH PERFORMANCE REINFORCMENT FOR USE IN INDUSTRIAL APPLICATIONS OFFERS EXCELLENT RESISTANCE TO ALKALISATION

All information stated within this Product Data Sheet is intended for reference purposes only The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.

