



**PRODUCT DATA SHEET**



# Admiral

## H938 TRANSFER TAPE

CHARACTERISTIC	VALUE
ADHESIVE	HIGH PERFORMANCE ACRYLIC
TACK	J.DOW NO. 12
LINER	90G/M2 GLASSINE RELEASE LINER, HONEY COLOUR
CARRIER	UNSUPPORTED
PEEL ADHESION	PSTC-3 2.5KGS/25MM
SHEAR STRENGTH	PSTC-7 OVER 48 HOURS WITH 1KG LOADING ON 25MM X 25MM
THICKNESS	0.1 ± 0.005MM
HEAT RESISTANCE	OVER 24 HOURS WITH 0.5KG LOADING ON 25MM X 25MM AT 70°C
SERVICE TEMPERATURE	-40 TO 110°C

### PRODUCT FEATURES AND APPLICATIONS

EXCEPTIONAL ADHESIVE PERFORMANCE OFFERING GOOD TEMPERATURE AND  
CHEMICAL RESISTANCE  
EXCELLENT FOR BONDING LOW ENERGY SURFACES AND ACHIEVING  
VERY GOOD LAMINATING RESULTS

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.