

 **PRODUCT DATA SHEET**

Admiral



H964 DOUBLE COATED UPVC TAPE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC (SOLVENT BASED)
LINER	90G/M2 HONEY GLASSINE RELEASE
CARRIER	0.05MM UNPLASTICISED PVC FILM
PEEL ADHESION	PSTC-3 2.6KGS/25MM
LOOP TACK	FINAT-9 2.8KG/25MM
SHEAR STRENGTH	PSTC-7 OVER 72 HOURS WITH 1KG LOADING ON 25MM X 25MM AT 25°C
THICKNESS	0.21 ± 0.01MM
HEAT RESISTANCE	OVER 24 HOURS WITH 0.5KG LOADING ON 25MM X 25MM AT 70°C
TENSILE STRENGTH	MD 7.0KG/MM2↑ TD 4.5 KG/MM2↑
ELONGATION	MD 150 %↑ TD 120 %↑
SERVICE TEMPERATURE	-30 TO 90°C (SHORT TIME)

PRODUCT FEATURES AND APPLICATIONS

PERMANENT BONDING RESULTS TO MOST SUBSTRATES, METAL, WOOD, GLASS,
CEMENT AND PLASTICS
EXTENSIVELY USED IN THE FURNITURE INDUSTRY ON PVC PROFILES
FASTENING FOR NAMEPLATES, LABELS AND EMBLEMS

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.