

 **PRODUCT DATA SHEET**

# Admiral



## H980 DIFFERENTIAL ADHESIVE DOUBLE COATED FOAM TAPE

CHARACTERISTIC	VALUE
ADHESIVE	DIFFERENTIAL RUBBER (SOLVENT BASED) CLOSED SIDE: REMOVABLE / OPEN SIDE: PERMANENT
LOOP TACK TEST FINAT-9	CLOSED SIDE: 1.0+0.1 OPEN SIDE: >5.0 (CARRIER BROKEN) KG/25MM
PEEL ADHESION PSTC-3	CLOSE SIDE: 0.8+0.1 OPEN SIDE: >3.0 (CARRIER BROKEN) KG/25MM
LINER	90G/M2 SUPERCALENDERED KRAFT PAPER
CARRIER	6 PCF PE FOAM
SHEAR STRENGTH	OVER 24 HOURS WITH 1KG SANDWICH LOADING ON 2 STAINLESS STEEL PLATES 25MM X 25MM AT 25°C
THICKNESS	0.8MM ± 0.1MM
SERVICE TEMPERATURE	-20 TO 60°C
COLOUR	WHITE

### PRODUCT FEATURES AND APPLICATIONS

DESIGNED FOR TEMPORARY FIXING AND JOINING, THE DIFFERENTIAL RUBBER ADHESIVE IS REMOVABLE ON THE CLOSED SIDE AND PERMANENT ON THE OPEN SIDE. REMOVES CLEANLY FROM MANY SURFACES WITHOUT LEAVING ANY RESIDUE.

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.