







H981 DOUBLE COATED FOAM TAPE

CHARACTERISTIC	VALUE
ADHESIVE	ACRYLIC (SOLVENT BASED)
TACK	J.DOW NO. 18
LINER	80G/M2 WHITE GLASSINE PAPER
CARRIER	CROSSLINKED 4 PCF PE FOAM
PEEL ADHESION	PSTC-3 2.8KGS/25MM
SHEAR STRENGTH	OVER 24 HOURS WITH 1KG SANDWICH LOADING
	ON 2 STAINLESS STEEL PLATES
	25MM X 25MM AT 25°C
THICKNESS	1.5MM ± 0.1MM
NORMAL TENSILE STRENGTH	OVER 20KG/25MM X 25MM
SERVICE TEMPERATURE	-20 TO 80°C
COLOUR	WHITE

PRODUCT FEATURES AND APPLICATIONS

HIGH TACK PERMANENT ADHESIVE WITH EXCELLENT AGING AND WEATHER RESISTANT PROPERTIES
SPECIFICALLY DESIGNED FOR MOUNTING AND JOINING NAMEPLATES, PLASTIC TRIM, SIGNS AND EMBLEMS
LONG TERM BONDING PERFORMANCE TO PLASTIC HANGERS AND MIRROR MOUNTING

All information stated within this Product Data Sheet is intended for reference purposes only The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.

