

PRODUCT DATA SHEET

❖ Storage condition:

- Temperature of 10 ~ 25 ° C, relative humidity of 50% ± 10%
- Store in the original packing and with the original protection materials
- Preferably no more than 6 layers if stored horizontally
- Do not expose in direct sunlight or heat sources

❖ Warranty:

- Shelf life: 1 year, stored in original carton box, preferably use within six months
- Prosecution Period: 1 year from the product manufacture date, no-acceptance for overdue product

❖ Technical Data:

Test Items	units	Average value
Thickness - PET	Micron	115 ± 10
Thickness - Liner	Micron	50 ± 10
Weight - finished production	g/m ²	250 ± 20
Gloss Rate 60°	%	≥ 90
Initial Adhesion	N/25mm	≥ 2
24h, 180°peel	N/25mm	≥ 3
Elongation at break	%	≥ 80
Dimensional stability	mm	≤ 0.1
Construction Temperature	°C	20 ± 10
Applicable Temperature	°C	-20 ~ +70

❖ Remarks:

- Information and technical data mentioned above are based upon practical knowledge and experience. The purchaser must assume all risks for any use, operation and application of the material. We are liable for damage only upon the amount of the purchase price under exclusion of indirect and accidental damage.
- All information given serves only to describe the product and is not to be regarded as assured properties in the legal sense.
- Specifications subject to change without notice, errors and omissions excepted.

INSTALLATION

Before applying an overlamine, we suggest you allow 24-48 hours for the print to dry. Always clean application free of dust, dirt, debris and other contaminants. We recommend cleaning the installation surface with isopropyl alcohol prior to application.

All information stated within this Product Data Sheet is intended for reference purposes only. The information does not suggest or constitute a verbal or written warranty. The end user shall be responsible for the testing and suitability of their application prior to final use.