

## TECHNICAL DATA SHEET

### SCDSB610 Double Sided Block Out Banner

---

Weight: 610gsm

❖ **Technical Data:**

Test Items	Test method	units	Average Data
Finished Thickness	GB/T 6672-2001	mm	0.45±0.02
Finished Fabric Weight	GB/T 4669-2008	Gram/m <sup>2</sup>	610 ± 20
E L a b Color	GB/T 2410-2008	△E	<1
PHR Level	GB/T 2410-2008	P	38P
Tensile Strength at Warp	GB/T 1040.1-2006& GB/T 1040.3-2006	MP	≥ 1500
Tensile Strength at Weft		MP	≥ 1500
Tearing strength at Warp	HG/T 2581.1-2009	N/5cm	≥ 220
Tearing strength at Weft		N/5cm	≥ 220
Peeling strength	GB/T 8425-2008	N/5cm	30
Service temperature range		°C	-20 ~ +70

APPLICATIONS

Indoor and outdoor double sided banners  
Exhibition double side banners  
Street pole banners

COMPATIBLE INK TECHNOLOGY

Solvent  
Latex  
UV Curable

FREE ROLL SLITTING SERVICE AVAILABLE



Unit 22 / 1029 Manly Rd, Tingalpa QLD 4173

P (07) 3890 5414 F (07) 3890 5701

ABN 49 163 849 232 ACN 163 849 232

[creativegraphicsupplies.com.au](http://creativegraphicsupplies.com.au)