

TECHNICAL DATA SHEET

SL440 Gloss Laminated Banner - Grey Back

Weight: 440gsm

Denier: 1000 x 1000

Yarn: 9 x 9

Property	Test Method	Value	Unit
Weight	+/- 5% tolerance	440	g/sm
Tensile Strength (warp/weft)	ISO 13934-1 : 2013 C.R.E.STRIP METHOD	1500 1130	N/50mm
Tearing Strength (warp/weft)	ISO 13937-2 : 2000 C.R.E.SINGLE TEAR METHOD	51 68	N
Elongation (warp/weft)	ISO 13934-1 : 2013 C.R.E.STRIP METHOD	27.5 28	%
Adhesion Strength (warp/weft)	ISO 2411 : 1991 C.R.E	59 67	N/50mm

APPLICATIONS

General rope & eyelet banners
Sail track signage & hoardings
Real estate skins

COMPATIBLE INK TECHNOLOGY

Solvent
Latex
UV Curable

AVAILABLE WIDTHS in 50m lengths

1370mm, 1600mm, 2600mm & 3200mm

FREE ROLL SLITTING SERVICE AVAILABLE



Unit 22 / 1029 Manly Rd, Tingalpa QLD 4173

P (07) 3890 5414 F (07) 3890 5701

ABN 49 163 849 232 ACN 163 849 232

creativegraphicsupplies.com.au